

TECHNICAL DESCRIPTION:

ENGINE BLOCK AND HEAD

- · Cast iron cylinder block
- One-piece cast iron cylinder head
- · Ladder frame fitted to engine block
- Replaceable wet cylinder liners and valve seats/ guides
- Drop forged crankshaft with induction hardened bearing surfaces and fillets with 7 main bearings
- 4 valve per cylinder layout with overhead camshaft and center position of unit injectors
- Each cylinder features cross-flow inlet and exhaust ducts
- Gallery oil cooled cast aluminium alloy pistons with three piston rings
- · Rear-end transmission

ENGINE MOUNTING

Flexible engine mounting

LUBRICATION SYSTEM

- · Integrated oil cooler in cylinder block
- Rear positioned twin full flow oil filter of spin-on type and by-pass

FUEL SYSTEM

- · Electronic high pressure unit injectors
- · Gear-driven fuel pump and injection timing
- Electronically controlled central processing system (EMS – Engine Management System)
- Single fine fuel filter of spin-on type

AIR INLET AND EXHAUST SYSTEM

- Twin entry turbo technology with freshwater cooled charge air cooler
- Air filter with replaceable inserts
- · Wet exhaust elbow/riser (option)

COOLING SYSTEM

- Seawater cooled plate heat exchanger
- · Coolant system prepared for hot water outlet
- Easily accessible seawater pump in rear end of flywheel housing

ELECTRICAL SYSTEM

 24V/110A alternator plus an optional extra 24V/110A alternator

INSTRUMENTS/CONTROLS

- Complete instrumentation including key switch and interlocked alarm
- EVC monitoring panels for single or twin installations
- · Electronic shift and throttle
- · Plug-in connectors
- · EVC system color display

BUKH SOLAS MARINE DIESEL ENGINE



D13-700 Specifications

| Engine type | D13 |
|------------------------------|---|
| Engine duty rating | C4 - Light Duty Commercial |
| Crankshaft power [hp(kW)] | 700 (515) |
| Rpm@full load | 2300 |
| Cylinders | In-line 6 |
| Displacement [L] | 12.78 |
| Bore [mm] | 131 |
| Stroke [mm] | - 158 - 158 |
| Compression ratio | 16.5:1 |
| Injection system | Electronic high pressure unit injectors |
| Alternator [V -A] | 24V – 110A |
| Electronic engine diagnostic | YES |
| Max. torque, NM @ 1200 rpm | 2930 |
| Dry Weight Bobtail [kg] | 1450 |
| Propulsion system | Shaft drive |
| | |

As BUKH is always endeavouring to improve the engines, specifications mentioned are subject to alterations without previous notice.

D13-700 Dimensions - with ZF325-1AE

Not for installation









