

The BUKH 4-cylinder D4-300 is developed from the latest design in modern diesel technology. The engine has common rail fuel injection system, double overhead camshafts, 4 valves per cylinder, turbocharger and aftercooler.

Together with a large swept volume and the EVC system (Electronic Vessel Control), this results in world-class diesel performance.

TECHNICAL DESCRIPTION:

ENGINE BLOCK AND HEAD

- Cast iron cylinder block and cylinder head
- Combined ladder frame and balance shaft
- 4 valve technology with hydraulic lash adjusters
- · Double overhead camshafts
- Oil cooled pistons with two compression rings and one oil scraper ring
- · Integrated cylinder liners
- Replaceable valve seats
- · Five bearing crankshaft
- Rear-end transmission

ENGINE MOUNTING

Flexible engine mounting

LUBRICATION SYSTEM

- Easily replaceable separate full-flow and by-pass oil filter
- Seawater cooled tubular oil cooler

FUEL SYSTEM

- Common rail fuel injection system
- Control unit for processing the injection
- Fine filter with water separator and alarm

AIR INLET AND EXHAUST SYSTEM

- Air filter with replaceable insert
- Crankcase gases vented into the air inlet
- Exhaust elbow or exhaust riser
- Freshwater cooled turbocharger
- Loss of sea water alarm

COOLING SYSTEM

- Thermostatically regulated freshwater cooling
- Tubular heat exchanger with separate large volume expansion tank
- Coolant system prepared for hot water outlet
- Easily accessible seawater impeller pump

ELECTRICAL SYSTEM

- 12V or 24V two-pole electrical system
- 14V/115A marine alternator with Zener-diodes to protect the system from peak voltage, and integrated charging regulator with battery sensor cable for maximum use of alternator
- Fuses with automatic reset
- Auxiliary stop button

INSTRUMENTS/CONTROLS

- Complete instrumentation/display packages, including e-key
- Electronic shift and throttle available as extras
- · Plug-in connections

D4-300

BUKH since 1899

BUKH SOLAS MARINE DIESEL ENGINE



D4-300 Specifications

Engine type	D4
Engine duty rating	C12 - High Speed Craft Commercial_3
Crankshaft power [hp(kW)]	300 (221)
Rpm@full load	3500
Cylinders	In-line 4
Displacement [L]	3,7
Bore [mm]	103
Stroke [mm]	110
Compression ratio	17.5:1
Injection system	Common Rail fuel injection system
Alternator [V -A]	14V - 115A
Electronic engine diagnostic	YES
Max. Fuel consumption [L/h]	58,4
Dry Weight Bobtail [kg]	483
Propulsion system	Shaft Drive / Waterjet

As BUKH is always endeavouring to improve the engines, specifications mentioned are subject to alterations without previous notice.

D4-300 Dimensions

Not for installation









